

Chicago  
Pneumatic

## Chipping Hammers

## CP-4123

**Applications:** This heavy-duty tool is designed for rugged use in foundries, fabrication shops and construction applications. The tool is available in 1" through 4" stroke versions, which offer the power levels necessary for a variety of uses, from light to medium chipping and trimming through heavy cutting.

## Features

- Simplate valve – for smooth, powerful operation
- Rugged construction – hardened steel piston, cylinder and handle
- Teasing throttle – for precise control
- Clip lock – prevents loosening of handle/cylinder
- Choice of bushing:
  - round – chisel freely rotates
  - hex – prevents chisel rotation



CP-4123-PYRA

All Models: pistol grip handle with self-closing outside trigger, 3/8" (NPTF) air inlet thread; air consumption at 90 psi, 23 - 27 cfm.

## CP-4125-PY

**Applications:** This heavy-duty tool is designed for rugged use in foundries, shipyards, refineries, fabrication shops and construction applications. Available in 1" through 4" stroke versions to offer the power levels necessary for a variety of uses from light and medium chipping and trimming through heavy cutting.

## Features

- Simplate valve - powerful, smooth running hammer with excellent controllability
- Teasing throttle – provides precise control
- Spline lock – prevents loosening of handle/cylinder
- Forged steel handle – withstands rugged use
- Heat treated cylinders with chrome plated bores – ensure excellent durability
- Choice of bushing:
  - round – chisel freely rotates
  - hex – prevents chisel rotation

<http://www.DesoutterTools.com>

## Lou Zampini &amp; Associates

37 Conifer Drive

North Providence, RI 02904-3020

1 800 353 4676

FAX 1 401 353 0113

Catalog Number	Part Number	Bore and Stroke mm (in.)	Blows per Minute	Chisel Bushing mm (in.)	Overall Length mm (in.)	Net Weight kg (lb.)
<b>SIMPLATE VALVE</b>						
CP-4123-PYBA	T021330	28.6 x 25.4 (1 1/8 x 1)	2820	17.3 (.680) Round	308 (12 1/8)	5.5 (12)
CP-4123-PYBE	T021331	28.6 x 25.4 (1 1/8 x 1)	2820	14.7 (.580) Hex.	308 (12 1/8)	5.5 (12)
CP-4123-PYRA	T021305	28.6 x 51 (1 1/8 x 2)	2400	17.3 (.680) Round	327 (12 7/8)	5.9 (13)
CP-4123-PYRE	T021588	28.6 x 51 (1 1/8 x 2)	2400	14.7 (.580) Hex.	327 (12 7/8)	5.9 (13)
CP-4123-PYSA	T021306	28.6 x 76 (1 1/8 x 3)	1920	17.3 (.680) Round	378 (14 7/8)	6.5 (14 1/4)
CP-4123-PYSE	T021587	28.6 x 76 (1 1/8 x 3)	1920	14.7 (.580) Hex.	378 (14 7/8)	6.5 (14 1/4)
CP-4123-PYTA	T024046	28.6 x 102 (1 1/8 x 4)	1500	17.3 (.680) Round	410 (16 1/8)	7.0 (15 1/2)
CP-4123-PYTE	T024047	28.6 x 102 (1 1/8 x 4)	1500	14.7 (.580) Hex.	410 (16 1/8)	7.0 (15 1/2)
CP-4125-PYBA	T020760	28.6 x 25.4 (1 1/8 x 1)	2820	17.3 (.680) Round	308 (12 1/8)	5.5 (12)
CP-4125-PYBE	T020832	28.6 x 25.4 (1 1/8 x 1)	2820	14.7 (.580) Hex.	308 (12 1/8)	5.5 (12)
CP-4125-PYRA	T020803	28.6 x 51 (1 1/8 x 2)	2400	17.3 (.680) Round	327 (12 7/8)	5.9 (13)
CP-4125-PYRE	T020804	28.6 x 51 (1 1/8 x 2)	2400	14.7 (.580) Hex.	327 (12 7/8)	5.9 (13)
CP-4125-PYSA	T020805	28.6 x 76 (1 1/8 x 3)	1920	17.3 (.680) Round	378 (14 7/8)	6.5 (14 1/4)
CP-4125-PYSE	T021296	28.6 x 76 (1 1/8 x 3)	1920	14.7 (.580) Hex.	378 (14 7/8)	6.5 (14 1/4)
CP-4125-PYTA	T020806	28.6 x 102 (1 1/8 x 4)	1500	17.3 (.680) Round	410 (16 1/8)	7.0 (15 1/2)
CP-4125-PYTE	T021297	28.6 x 102 (1 1/8 x 4)	1500	14.7 (.580) Hex.	410 (16 1/8)	7.0 (15 1/2)

**Standard equipment:** All Models: Economy retainer, P107243 accepts oval collar chisels. Wire retainer spring, P070994.

**Optional equipment:** All Models: hose swivels and chisel retainers.