

Impulse – Shut Off and Non Shut Off



Lou Zampini & Associates
 2 Douglas Pike, Rt. 7
 Smithfield, RI 02917
 1 800 353 4676
 FAX 1 401 679 0165

NON SHUT OFF

PICTURE REF	TOOL TYPE	PART NUMBER	FREE SPEED	OUTPUT	TORQUE RANGE	LENGTH	WEIGHT	AIR FLOW	AIR HOSE BORE	AIR INLET ⁽¹⁾	SOUND LEVEL ⁽²⁾	VIBRATION
			r/min	hex	Nm	mm	kg	l/s	mm	BSP	dB(A)	ms ²
A	PT008-L10500-I4Q	1461384	10500	1/4" hex	4-8	238	0.95	5	8	1/4"	72	<2.5
A	PT013-L10500-I4Q	1461394	10500	1/4" hex	8-13	263	1.0	5	8	1/4"	72	<2.5
B	PT030-L9000-I10S	1461404	9000	3/8" sq	15-30	246	1.2	5	8	1/4"	73	<2.5
C	PT009-T7800-I4Q	1461414	7800	1/4" hex	5-9	184	0.95	6	8	1/4"	76	<2.5
C	PT016-T7800-I4Q	1461784	7800	1/4" hex	9-16	208	1.05	6	8	1/4"	76	<2.5
D	PT035-T9000-I10S	1461424	9000	3/8" sq	20-35	175	0.98	6	8	1/4"	77	<2.5
E	PT070-T7500-I13S	1461434	7500	1/2" sq	42-70	179	2.0	7	8	1/4"	79	<2.5
F	PT115-T6000-I13S	1461444	6000	1/2" sq	75-115	185	2.7	9	10	3/8"	78	2.5
F	PT200-T5500-I13S	1461454	5500	1/2" sq	120-200	181	3.3	11	10	3/8"	81	2.7
F	PT250-T4000-I19S	1461464	4000	3/4" sq	160-250	232	4.3	12	10	3/8"	80	4.5

SHUT OFF

PICTURE REF	TOOL TYPE	PART NUMBER	FREE SPEED	OUTPUT	TORQUE RANGE	LENGTH	WEIGHT	AIR FLOW	AIR HOSE BORE	AIR INLET ⁽¹⁾	SOUND LEVEL ⁽²⁾	VIBRATION
			r/min	hex	Nm	mm	kg	l/s	mm	BSP	dB(A)	ms ²
G	PT010-L5000-S4Q	1462254	5000	1/4" hex	5-10	212	0.9	6	8	1/4"	74	<2.5
G	PT014-L6000-S4Q	1462264	6000	1/4" hex	8-14	212	0.9	6	8	1/4"	74	<2.5
H	PT010-T5500-S4Q	1462274	5500	1/4" hex	5-10	166	0.95	6	8	1/4"	74	<2.5
H	PT014-T6000-S4Q	1462284	6000	1/4" hex	8-14	166	1	6	8	1/4"	74	<2.5
I	PT040-T6000-S10S	1462294	6000	3/8" sq	22-40	177	1.4	8	8	1/4"	77	<2.5
J	PT070-T4000-S13S	1462304	4000	1/2" sq	32-70	192	1.8	10	10	1/4"	81	<2.5
K	PT125-T3500-S13S	1462314	3500	1/2" sq	62-125	201	2.4	12	10	1/4"	81	3.3

⁽¹⁾ NPT optional

⁽²⁾ Sound level measured to test code PN8NCT1.2