


## D Series

### Button start – push/pull reverse



D16-S

TOOL TYPE	PART NUMBER	FREE SPEED	REVERSE SPEED	CHUCK SIZE	MAX. TAPPING TORQUE	LENGTH	AIR FLOW	MIN. HOSE BORE	AIR INLET	WEIGHT	SOUND LEVEL
		r/min	r/min	mm	Nm	mm	l/s	mm	BSP	kg	dB(A)
D16-S-1000	1274544	1000	2000	6.5	4.3	299	9.4	10	1/4"	1.3	77
D16-S-500	1274384	500	1000	10	8.6	310	9.4	10	1/4"	1.4	77

Vibration level <math><2.5\text{ms}^{-2}</math>



D16-L

### Lever start – push/pull reverse

TOOL TYPE	PART NUMBER	FREE SPEED	REVERSE SPEED	CHUCK SIZE	MAX. TAPPING TORQUE	LENGTH	AIR FLOW	MIN. HOSE BORE	AIR INLET	WEIGHT	SOUND LEVEL
		r/min	r/min	mm	Nm	mm	l/s	mm	BSP	kg	dB(A)
D16-L-1000	1274624	1000	2000	6.5	4.3	299	9.4	10	1/4"	1.3	77
D16-L-500	1274464	500	1000	10	8.6	310	9.4	10	1/4"	1.4	77

Vibration level <math><2.5\text{ms}^{-2}</math>



D16-P

### Trigger start – push/pull reverse

TOOL TYPE	PART NUMBER	FREE SPEED	REVERSE SPEED	CHUCK SIZE	MAX. TAPPING TORQUE	LENGTH	AIR FLOW	MIN. HOSE BORE	AIR INLET	WEIGHT	SOUND LEVEL
		r/min	r/min	mm	Nm	mm	l/s	mm	BSP	kg	dB(A)
D16-P-750	1288084	750	1500	6.5	6.2	297	8.5	10	1/4"	1.7	78
D16-P-450	1287934	450	900	10	11.1	308	8.5	10	1/4"	1.8	78

Vibration level <math><2.5\text{ms}^{-2}</math>

## F Series

### Lever start – button reverse – stand mounted



2F16-L

TOOL TYPE	PART NUMBER	FREE SPEED	REVERSE SPEED	CHUCK SIZE	MAX. TAPPING TORQUE	LENGTH	AIR FLOW	MIN. HOSE BORE	AIR INLET	WEIGHT	SOUND LEVEL
		r/min	r/min	mm	Nm	mm	l/s	mm	BSP	kg	dB(A)
2F16-L-700	1241394	700	700	6.5	6.7	279	11.1	10	1/4"	1.7	76
2F16-L-250	1241474	250	250	6.5	17.5	298	11.1	10	1/4"	1.8	76

Vibration level <math><2.5\text{ms}^{-2}</math>

## Deburring tools

### Push start – variable speed



A27-A C27-AX

TOOL TYPE	PART NUMBER	FREE SPEED	COLLET SIZE FITTED	AIR FLOW	MIN. HOSE BORE	AIR INLET	LENGTH	WEIGHT	SOUND LEVEL	VIBRATION LEVEL
		r/min	mm	l/s	mm	BSP	mm	kg	dB(A)	ms <sup>-2</sup>
A27-A-1300	1406594	100-1300	Ø4	2.4	3	M5	172	0.24	64	2.5
C27-AX-1450	1405414	100-1450	Ø6	6.2	6	1/4"	218	0.48	73	4.3



D156-S

## Rivet Millers

TOOL TYPE	PART NUMBER	FREE SPEED	Ø MAXIMUM CUTTER	AIR FLOW	MIN. HOSE BORE	AIR INLET	LENGTH	WEIGHT	SOUND LEVEL	VIBRATION LEVEL
		r/min	mm	l/s	mm	BSP	mm	kg	dB(A)	ms <sup>-2</sup>
D156-S-20000	1275194	20000	14.3	9.3	10	1/4"	232	1.0	77	<math><2.5</math>
D156-P-20000	147664	20000	14.3	9.3	10	1/4"	203	1.1	78	<math><2.5</math>

For accessories see page 44